

Detail & Submittal Sheet




Project: _____
 Specification Reference: _____
 Model Number: _____ Quantity: _____
 Architect: _____
 Contractor: _____
 Distributor: _____
 Approved By: _____
 Date: _____

CO2 Aluminum Cylinder Carbon Dioxide

- CO₂ squeeze grip operation
- Strong impact resistant horn
- Aluminum cylinder – complete with wall bracket
- Stainless steel hose band
- **6 YEAR WARRANTY**
- Meets or exceeds ANSI/UL 711, ANSI/UL 154
- Individually packaged

Solid Brass Valve



CO2-20


CO2-1

5CO2-10

CO2-5

RELATED PRODUCT

Strike First Heavy Duty Bracket



Seamless steel construction for heavy duty strength



032 HDVB4

Class B: Flammable Liquids such as Gasoline, Oil, Paints, Solvents, etc...
Class C: Live electrical equipment



NOTE: Standard brackets are included with all extinguishers at no additional cost. If specified, optional brackets are only available at additional cost. All of the brackets are designed to accommodate Strike First Corporation of America extinguishers. Most comparably

sized extinguishers usually will function with these brackets, Strike First Corporation of America cannot assume responsibility for variations in cylinder dimensions among various extinguisher suppliers.

Model #	UL Description	Discharge Time	Capacity	Weight	Diameter	Height	Width	PSI	Range	Temp. Range	U/L Rating	Coast Guard Approved/Bracket #
		sec.	lbs	lbs/kgs	in/cm	in/cm	in/cm		feet/meters	°F/°C		
CO2 Extinguishers												
CO2-5	SF-5CO2A	10	5 lb	13 1/4 lbs 6.12 kgs	5 1/4" 13.3 cm	17 1/4" 44 cm	8 1/2" 21.6 cm	-	6-12 2-2.5m	-22°F-120°F -30°C-49°C	5BC	Yes HDVB-2
CO2-10	SF-10CO2A	10	10 lb	28 lbs 12.7 kgs	7" 17.8 cm	19 3/4" 50.2 cm	11 3/4" 30 cm	-	6-12 2-2.5m	-22°F-120°F -30°C-49°C	10BC	Yes HDVB-3
CO2-15	SF-15CO2A	15	15 lb	37 lbs 12.3 kgs	7" 17.8 cm	26 1/4" 66.7 cm	11 3/4" 30 cm	-	6-12 2-2.5m	-22°F-120°F -30°C-49°C	10BC	Yes HDVB-3
CO2-20	SF-20CO2A	20	20 lb	48 1/8 lbs 21.8 kgs	8" 21 cm	26 1/4" 66.7 cm	12" 30.5 cm	-	6-12 2-2.5m	-22°F-120°F -30°C-49°C	10BC	-

